



A CSW Industrials Company

SAFETY DATA SHEET

METACALK® 835+
Elastomeric, silicone firestop sealant

SECTION 1 - PRODUCT AND COMPANY INFORMATION

Product name

Metacaulk 835+

Product Codes

66645, 66300, 66301, 66019

Chemical Family

Organic/Inorganic

Use

Firestopping sealant

Manufacturer's Name

RectorSeal LLC
2601 Spenwick Drive
Houston, Texas 77055 USA

Date of validation

July 21, 2020

Date of Preparation

April 15, 2019

HMIS Codes

Health 1
Flammability 2
Reactivity 0
PPI B

Emergency Telephone No.

Chemtrec 24 Hours
(800) 424-9300 USA
(703) 527-3887 International

Technical Service Telephone No.

(800) 231-3345 or (713) 263-8001

SECTION 2 - HAZARDS IDENTIFICATION

GHS CLASSIFICATION

Physical Hazards:

None

Health Hazards:

Eye irritation – Category 2B
Skin irritation – Category 2
Skin sensitization– Category 1B

Environmental Hazards:

Hazardous to the Aquatic Environment: Not Classified
Acute aquatic toxicity: Not Classified
Chronic aquaitc toxicity: Not Classified
Bioaccumulation potential: Not Classified
Rapid degradability: Not Classified

GHS Label elements, including precautionary statements



GHS07: Harmful
Signal Word: Warning

Hazard Statements:

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes eye irritation

Precautionary Statements:

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust, fume or vapors.
P262 - Do not get in eyes, on skin or on clothing.
P264 - Wash hands and other skin areas thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352+P333+P313 If on skin: wash with plenty of soap and water. If skin irritation or rash occurs, get medical attention.
P305+P351+P338 If in eyes: rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313 If exposed or concerned: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P321 Specific treatment: Seek immediate medical advice. Refer to product label and Section 4 of this SDS.
P362 Take off contaminated clothing and wash it before reuse.

Storage:

P405+P403 Store locked up. Store in a well-ventilated place.

Disposal:

P501 Dispose of contents and container in accordance with applicable local, regional, national and international regulations

SUMMARY OF ACUTE HAZARDS

May cause skin/eye irritation and an allergic skin reaction.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION

Not known to be a respiratory irritant. Prolonged inhalation may be harmful.

EYE CONTACT

Contact may cause eye irritation.

SKIN CONTACT

Contact may cause skin irritation.

INGESTION

Possible irritation to mucous membranes of the mouth, throat, and stomach.

SUMMARY OF CHRONIC HAZARDS

None known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Persons with pre-existing skin conditions or chemical allergies may be more susceptible to contact effects of the cured elastomer.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient: Calcium Carbonate

Percentage by weight: 15 -40

Cas Number: 1317-65-3

Ingredient: 2-Butanone, O, O', O"- (methylsilylydyne) trioxime

Percentage by weight: 3 - 7

Cas Number: 22984-54-9

Ingredient: Silica 2482, hydrophobic

Percentage by weight: 3 - 7

Cas Number: 7631-86-9

Ingredient: Titanium Dioxide

Percentage by weight: 0.1 – 1.0

Cas Number: 13463-67-7

SECTION 4 - FIRST AID MEASURES

If INHALED	Not a respiratory irritant.
If on SKIN	Wash with soap and water. If irritation occurs, seek medical attention.
If in EYES	Immediately flush with large amounts of water. If irritation occurs, seek medical attention.
If SWALLOWED	If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Heat may build up and rupture closed containers.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Wipe up spills to prevent footing hazard. Avoid flushing into sewers, drains, waterways and soil.

Wear protective clothing during clean up.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep container closed and upright when not in use. To prevent freezing and possible rupture of container, do not store below 35 F.

OTHER PRECAUTIONS:

Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues and vapors; treat as if full and observe all product precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredient	Units
2-Butanone, O, O', O''- (methylsilylydyne) trioxime	
ACGIH TLV	10 ppm
OSHA PEL	N/D ppm

Calcium carbonate

ACGIH TLV N/D ppm
 OSHA PEL 15 mg/m3

Silica 2482, hydrophobic

ACGIH TLV N/D ppm
 OSHA PEL 10 mg/m3

Titanium Dioxide

ACGIH TLV 10 mg/m3 A4 ppm
 OSHA PEL 15 mg/m3

RESPIRATORY PROTECTION (SPECIFY TYPE): None required.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: N/A

MECHANICAL (GENERAL): Preferable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: Not available

Specific Gravity (H₂O = 1): 1.001 - 1.005 at 25 °C (77 °F)

Vapor Pressure (mm Hg): Less than 5 mm Hg

Melting Point: N/A

Vapor Density (Air = 1): N/A

Evaporation Rate (Ethyl Acetate = 1): >1

Appearance/Odor: Viscous paste

Solubility In Water: N/A

Volatile Organic Compounds (VOC) Content 25 grams per liter, <3% by weight
 (Chemically Curing Sealants and Caulks – CARB Method 310:
 VOC less water, less exempt compounds and LVP-VOCs).

Flash Point: None

Lower Explosion Limit: None

Upper Explosion Limit: None

SECTION 10 - STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: None

Incompatibility (Materials to Avoid): None Known.

Hazardous Decomposition Products: CO, CO₂ and fragmented hydrocarbons.

Hazardous Polymerization: Will not occur.

SECTION 11 - TOXICOLOGY INFORMATION

Toxicology Data

Ingredient Name

**2-Butanone, O,O',O"-
(Methylsilylidyne) trioxime**

Oral-Rat LD50: 2463 mg/kg
Dermal-Rat LC50: >2000 mg/kg

Calcium carbonate

Oral-Rat LD50: >6450 mg/kg
Dermal-Rat LD50: NA

Silica 2482, hydrophobic

LC50-rat, dust >2.08 mg/L
Oral-Rat LD50: >3300 mg/kg
Dermal-Rabbit LD50: >5000 mg/kg

Titanium dioxide

LC50 -rat >6820 mg/kg (rat) (4-hour exposure)
Oral-Rat LD50: > 25000 mg/kg (rat)
Dermal LD50: > 1000 mg/kg (rabbit)

SECTION 12 - ECOLOGICAL INFORMATION

Ecological Data

Ingredient Name:	Ketoximane Silane	
Toxicity to fish:	LC50 (<i>Oncorhynchus mykiss</i> (rainbow trout)):	>120 mg/L, 96 hrs.
Toxicity to daphnia and other aquatic invertebrates:	EC50 (<i>Daphnia magna</i> (water flea)):	>120 mg/L, 48 hrs.
Ingredient Name:	Titanium Dioxide	
Toxicity to fish:	C50 (<i>Oncorhynchus mykiss</i> (rainbow trout)):	>100 mg/L, 96 hrs.
Toxicity to daphnia and other aquatic invertebrates:	EC50 (<i>Daphnia magna</i> (water flea)):	>120 mg/L, 48 hrs.
Toxicity to algae:	EC50 (<i>Skeletonema costatum</i> (marine diatom)):	>10,000 mg/L, 72 hrs.
Toxicity to bacteria:	EC50:	>1,000 mg/L, 3 hrs.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Classification: Non-regulated solid waste

Disposal Method: Approved landfill

Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

SECTION 14 - TRANSPORTATION INFORMATION

DOT:	Non-Regulated
OCEAN (IMDG):	Non-Regulated
AIR (IATA):	Non-Regulated
WHMIS (CANADA):	Non-Regulated

SECTION 15 - REGULATORY INFORMATION

Regulatory Data

Ingredient:	Amorphous Silica
SARA 313	N/A
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A
Ingredient:	Ketoxime Silane
SARA 313	N/A
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A
Ingredient:	2-Butanone, O,O',O'',O'''-silanetetrayltetraoxime
SARA 313	N/A
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A
Ingredient:	N-[3-(Trimethoxysilyl)propyl]ethylenediamine
SARA 313	N/A
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A
Ingredient:	Titanium Dioxide
SARA 313	N/A
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A

SECTION 16 - OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001